

LUXDSIGN SILENCIO 5 WHITE PTX

 PVC-free, recyclable

TECHNICAL SPECIFICATIONS

Material	100% Trevira CS weave fabrics
Finished material weight	300 g/m ² (approx.)
Thickness	1400 µm (approx.)
Fire Classification	B-s1, d0 - DIN EN 13501-1 Class A - ASTM E84-16 NFPA 701
Trapezoid tear resistance	warp: 1794.2 N weft: 1207.5 N DIN EN ISO 1421
Maximum tensile strength	warp: 41.4% weft: 22.8% DIN EN ISO 1421
Stretchability	warp: 0.4% cross: 0.3% DIN EN 14704-1

Cut

- Cold cut
- Ultrasonic cut

Printing

- Inside: UV, Latex
- Outside: UV, Latex

We reserve the right for technical modifications.
The above mentioned details are non-binding. A tolerance of ± 5% is valid.

Le informazioni pubblicate riguardanti i nostri prodotti sono basate su conoscenze ed esperienze pratiche. Gli acquirenti devono indipendentemente determinare, prima dell'uso, l'idoneità del materiale per l'utilizzo che ne vogliono fare. L'acquirente deve assumersi tutti i rischi per qualsiasi uso, funzionamento e applicazione del materiale. Noi siamo responsabili del

Application Areas

- Digital printing/art reproduction
- Exhibition
- Display system
- Textile construction
- Stage/show/event
- Acoustic fabric
- Visual merchandising
- Stretch ceiling

Certifications

Acoustic absorption value α_w /class*: 0.85/B
Type of assembly E-50 according to DIN EN ISO 354. Textile in front of total 50 mm, included 2 x 20 mm ISOVER SSP 2 and 10 mm airspace.

