

LUXTEX ARTIST HEAVY PTX



TECHNICAL SPECIFICATIONS

Material	100% polyester weave fabrics
Finished material weight	280 g/m ² (approx.)
Thickness	400 µm(approx.)
Fire Classification	B-s1, d0 - DIN EN 13501-1
Trapezoid tear resistance	warp: 1831.6 N weft: 2288.7 N DIN EN ISO 13934-1
Maximum tensile strength	warp: 60.7% weft: 32.3% DIN EN ISO 13934-1
Stretchability	warp: 0.6% cross: 0.3% DIN EN 14704-1
Luminous characteristics	blank: 26.9% DIN EN 410
Solar characteristics	blank: 0.0% DIN EN 410
Luminous reflectance	blank: 91.01 DIN 5033-1

Application Areas

- Display system
- Exhibition
- Backlit
- Digital printing/art reproduction
- Stage/show/event
- Visual merchandising
- Textile construction

Cut

- Cold cut
- Heat cut
- Ultrasonic cut

Certifications



Printing

- Inside: UV, Latex, Solvent

We reserve the right for technical modifications.

The above mentioned details are non-binding. A tolerance of ± 5% is valid.

Le informazioni pubblicate riguardanti i nostri prodotti sono basate su conoscenze ed esperienze pratiche. Gli acquirenti devono indipendentemente determinare, prima dell'uso, l'idoneità del materiale per l'utilizzo che ne vogliono fare. L'acquirente deve assumersi tutti i rischi per qualsiasi uso, funzionamento e applicazione del materiale. Noi siamo responsabili del

danno solo per il prezzo d'acquisto con esclusione di danni diretti o accidentali. Tutte le informazioni fornite servono solo a descrivere il prodotto e non riguardano assicurazioni in senso giuridico. Le specifiche sono soggette a modifiche senza preavviso, salvo errori ed omissioni.