

LUXPRINT PP WHITE BACK



Introduction

- Base substrate: PP in 170 micron
- Coated: Acrylic 25 micron
- Ink absorption: Solvent, ECO solvent, UV, Latex
- Durability: Up to 2 years

Advantages

- Economical and environmental friendly roll up solution & scrolling light box material

FEATURES

Substrate	170 µm DIN60001
Substrate density	0.7
Finished weight	144 g/m ² DIN EN ISO 2286-2
Finished Thickness	195 ± 5 µm
Coating Thickness	20 µm
Coating peeling strength	No peeling GB/T1040
Whiteness	92
Glossiness	86/8
Min Storage Temperature	-70 / -94 °C / °F
Temperature range	-70 ~ +80 °C DIN53372

Le informazioni pubblicate riguardanti i nostri prodotti sono basate su conoscenze ed esperienze pratiche. Gli acquirenti devono indipendentemente determinare, prima dell'uso, l'idoneità del materiale per l'utilizzo che ne vogliono fare. L'acquirente deve assumersi tutti i rischi per qualsiasi uso, funzionamento e applicazione del materiale. Noi siamo responsabili del

danno solo per il prezzo d'acquisto con esclusione di danni diretti o accidentali. Tutte le informazioni fornite servono solo a descrivere il prodotto e non riguardano assicurazioni in senso giuridico. Le specifiche sono soggette a modifiche senza preavviso, salvo errori ed omissioni.